



3M



3M™ Industrial Painter's Tape 205

Time is money, and the best way to save is doing a job right the first time. Professionals keep coming back to 3M Products, because they know that using highly reliable 3M tapes is the best defence against costly rework. 3M Industrial Painter's Tape 205 delivers excellent results at an exceptional value.

- Crepe paper backing contains 30% post consumer recycled fibre 3M™ Industrial Painter's Tape 205
- Compatible with most solvent based paints, latex paints and lacquers paints
- Up to 5 days clean removability
- Easy removal resists damages to surfaces
- Good holding power to help resist lifting or curling
- Easy controlled unwind
- Resists paint bleed



Part No.	Size	PRICE
258 205-12MM	12mm x 55mm	\$1.03
258 205-18MM	18mm x 55mm	\$1.39
258 205-24MM	24mm x 55mm	\$1.66
258 205-36MM	36mm x 55mm	\$2.50
258 205-48MM	48mm x 55mm	\$3.33
258 205-72MM	72mm x 55mm	\$4.99

Application Methods

Avoid stretching tape: Pull tape off roll a few feet at a time and press down a small area without stretching.

Press edge of tape down firmly: For best paint lines, press firmly on tape with putty knife.

Irregular Surfaces

Lay tape into surface depressions: If it is stretched and forced down, the tape may lift up or, in some cases, break.



Removal Methods

Speed of removal: Moderate speeds are best. Excessive rate of removal may cause tearing. Very slow rate of removal increases tendency to transfer adhesive.

Angle of removal: A 45° angle works best. Remove tape back on itself as shown in illustration.

